



# SAC305

# MSDS

|                   |  |                        |  |
|-------------------|--|------------------------|--|
| SAC305            |  | Lead-Free Solder Paste |  |
| 0769-38893080-852 |  | 0769-81360133-852      |  |
| ChenM@dglzd.com   |  | : 13827200149          |  |
| MSDS-1004         |  | 2014.07.01             |  |

| ( )                 |              |          | (CAS NO.)                              |
|---------------------|--------------|----------|--|
| (Rosin)             | ---          | 3.6-5.4% | 8050-09-7                              |
| (Solvent)           | ---          | 1.8-3.6% | 112-59-4                               |
| (Additive)          | ---          |          | ---                                    |
| (tin) silver copper | SnAg3.0Cu0.5 | 88%      | Sn7440-31-5 Ag7440-22-4<br>Cu7440-50-8 |
| ---                 |              |          |  |

|  |  |  |
|--|--|--|
|  |  |  |
|  |  |  |
|  |  |  |
|  |  |  |
|  |  |  |
|  |  |  |

|    |  |
|----|--|
| 15 |  |
|----|--|



|  |
|--|
|  |
|  |
|  |
|  |

|  |
|--|
|  |
|  |
|  |
|  |

|  |
|--|
|  |
|  |
|  |
|  |

|    |
|----|
|    |
| 1. |
| 2. |
| 3. |
|    |
|    |

|             |        |           |                        |                        |
|-------------|--------|-----------|------------------------|------------------------|
|             |        |           |                        |                        |
|             |        |           |                        |                        |
| (TWA)       | (SGEL) | (Ceiling) | LD50<br>(            ) | LC50<br>(            ) |
| Sn:2.0mg/m3 | -----  | -----     | -----                  | -----                  |



|       |
|-------|
| / ( ) |
|-------|

|                      |         |       |  |       |
|----------------------|---------|-------|--|-------|
|                      |         |       |  |       |
|                      | pH      |       |  |       |
|                      |         |       |  |       |
|                      | 217-219 |       |  |       |
| -----                |         |       |  |       |
|                      |         | (LEL) |  | (UEL) |
| ( )                  | (21.1 ) |       |  |       |
| 7.4g/cm <sup>3</sup> |         |       |  |       |

|        |  |  |  |  |
|--------|--|--|--|--|
|        |  |  |  |  |
|        |  |  |  |  |
|        |  |  |  |  |
| (752%) |  |  |  |  |

|                                |  |  |  |  |
|--------------------------------|--|--|--|--|
| ( )~NIF (No Information Found) |  |  |  |  |
| ---                            |  |  |  |  |
| ---                            |  |  |  |  |
| ---                            |  |  |  |  |
| ---                            |  |  |  |  |

|         |  |  |  |  |
|---------|--|--|--|--|
| ( )~NIF |  |  |  |  |
| /       |  |  |  |  |



( )

INTERNATIONAL MARITIME DANGEROUS GOODS CODE LABEL  
DO'T SHIPPING LABEL  
DO'T SHIPPING NAME

| AIR PRODUCTS MSDS |      |      | INTERNATIONAL MARITIME DANGEROUS GOODS CODE  |   |   |   |   |
|-------------------|------|------|--|---|---|---|---|
|                   | NFPA | HMIS | 0  | 1 | 2 | 3 | 4 |
|                   | 1    | 1    | NFPA National Fire protection Association rating identifies hazards during a fire emergency. |   |   |   |   |
|                   | 0    | 0    |  |   |   |   |   |
|                   | 0    | 0    | HMIS Hazardous Materials Identification System rating applies to process as packaged.        |   |   |   |   |